

THRASHER H/T HTD01

The Thrasher H/T is for those that prefer to have their vehicle operate with a quiet, comfortable ride on their daily commute or loaded up for work and play. The Thrasher H/T features generous size tread blocks for traction, and staggered tread pattern with reduced voids to dampen road noise. Durable, comfortable, consistent performance are all trusted attributes with the Ironhead Thrasher H/T.



50,000 Mile Limited Treadwear Warranty.
See our Warranty for full details.
Mileage Warranty does not apply to LT tires.

TRUSTED PERFORMANCE

The wide tread surface is designed with multiple siping for consistent wet and dry traction, predictive handling and better braking performance.

DURABILITY

Advanced mixing technology used to engineer proprietary rubber compounds allow fillers to be dispersed evenly to avoid irregular wear and enhance durability.

COMFORT

Shoulder design incorporates tie-bar design increasing handling stability, and reducing road noise.



WET PERFORMANCE



DRY PERFORMANCE



RIDE COMFORT



QUIETNESS



TREAD LIFE



THRASHER

H/T HTD01



SIZE	PR	LI/SR	T.D.	O.D.	S.W.	R.W.	UTQG	MAX LOAD 1X	MAX LOAD 2X
			32/in.	in.	in.	in.		LBS@PSI	LBS@PSI
235/75R15		105T	11	29.0	9.4	7	700 A A	2039@44	
235/70R16		106T	11	28.9	9.3	6.5	700 A A	2094@44	
245/75R16		111T	11	30.9	9.3	6.5	700 A A	2403@44	
265/75R16		116T	11	30.6	9.8	7	700 A A	2756@44	
235/75R17		109T	11	30.5	9.8	7	700 A A	2271@44	
245/70R17		110T	11	32.1	10.2	7.5	700 A A	2337@44	
265/70R17		115T	11	31.5	10.7	8	700 A A	2679@44	
255/70R18		113T	11	31.7	10.7	8	700 A A	2535@44	
265/65R18		114T	11	31.7	10.5	7.5	700 A A	2601@44	
275/65R18		116T	11	31.9	11.2	8.5	700 A A	2756@44	
275/55R20	XL	117T	11	33.0	11	8	700 A A	2833@50	
275/60R20		115T	11	32.1	11	8	700 A A	2679@44	
31X10.50R15LT	6PR	109R	14	30.5	10.6	8.5		2270@50	
LT215/85R16	10PR	115/112R	14	30.4	8.5	6		2680@80	2470@80
LT225/75R16	10PR	115/112R	14	29.3	8.8	6		2680@80	2470@80
LT235/85R16	10PR	120/116R	14	31.8	9.3	6.5		3042@80	2778@80
LT245/75R16	10PR	120/116R	14	31.7	9.3	6.5		3042@80	2778@80
LT265/75R16	10PR	123/120R	14	30.6	9.8	7		3415@80	3085@80
LT235/80R17	10PR	120/117R	14	30.5	9.8	7		3085@80	2835@80
LT245/70R17	10PR	119/116S	14	31.5	9.8	7		3000@80	2755@80
LT245/75R17	10PR	121/118S	14	31.7	10.7	8		3195@80	2910@80
LT265/70R17	10PR	123/120S	14	32.6	10.7	8		3415@80	3085@80
LT265/70R18	10PR	124/121S	14	31.7	10.5	7.5		3525@80	3195@80
LT275/65R18	10PR	123/120S	14	32.1	11	8		3415@80	3085@80
LT275/70R18	10PR	125/122S	14	34.1	11	8		3640@80	3305@80
LT275/65R20	10PR	126/123S	14	33.2	11	8		3750@80	3415@80