

THRASHER LMD

LAST MILE DELIVERY

Last Mile Delivery vehicles are everywhere, with continuous deliveries to both business and residential locations. These vehicles commonly endure many stops, starts, and turns as part of their regular day. The Thrasher LMD is engineered to withstand these daily demands and ensure a durable, reliable tire. Built with a purpose, a sidewall protector was added to ensure longevity for every fleet big and small. Like the vehicles they are on, the Thrasher LMD will get the job done.



FEATURES & BENEFITS

- Sidewall protectors to ensure longevity
- Deeper tread depth for longer life
- Wider footprint for improved stability
- Reinforced 10 ply construction increases carrying capacity over comparable LT sizes

*Note: 225/75R16C LCC = 3197 lbs vs. LT225/75R16 10PR = 2680 lbs

3 Sizes make up
90%
of the market and grew
+16% in 2023

Total LMD market
continue to grow
in the USA:
10%
vs 2022

* Source: USTMA PLT Shipments – 2023 vs 2022

SIZE	PR	LI/SR	T.D.	O.D.	S.W.	R.W.	MAX LOAD 1X	MAX LOAD 2X
			32/in.	in.	in.	in.	lbs@psi	lbs@psi
195/75R16C	8PR	107/105R	13	27.48	7.70	5.5	2149@69	2039@69
225/75R16C	10PR	121/120R	13	29.29	8.78	6.0	3197@83	3086@83
235/65R16C	10PR	121/119R	13	28.03	9.45	7.0	3197@83	2998@83

IH-ST

SPECIALTY TRAILER

The Ironhead IH-ST is a specialty trailer tire designed for towed trailer applications. With its radial construction, the Ironhead IH-ST is engineered to deliver long life and superior towing stability.

APPLICATIONS

- Utility Trailers
- Boat Trailer
- RV Trailers

TIRE FEATURES

- Radial construction provides strength and durability.
- Tread is designed to reduce excessive heat build up.
- Tread pattern delivers a stable and quiet ride.
- Rubber compound engineered to provide low rolling resistance.



SIZE	PR	LI	T.D.	S.R.	O.D.	S.W.	R.W.	MAX LOAD 1X	MAX LOAD 2X	AP
			32/in.	in.	in.	in.	in.	lbs@psi	lbs@psi	
ST175/80R13	6	91/87	10	L	24	7	5J	1,360	1,200	50
ST205/75R14	6	100/96	10	L	26.1	8	5 1/2J	1,760	1,570	50
ST215/75R14	6	102/98	10	L	26.7	8.5	6J	1,870	1,650	50
ST205/75R15	8	107/102	10	L	27.1	8	5 1/2J	2,150	1,870	65
ST225/75R15	10	117/112	10	L	28.3	8.8	6J	2,830	2,470	80
ST235/80R16	10	124/120	10	L	30.8	9.3	6 1/2J	3,520	3,080	80
ST235/85R16	12	128/124	10	L	31.7	9.3	6 1/2J	3,970	3,525	80